

## Master-PUR HX Trivolution

**PU Transport hose & Suction Hose, highly abrasion resistant and vacuum proof, with reinforcement underneath the spiral, antistatic, surface resistance <math> < 10^9 </math> Ohm, microbe-resistant, hardly inflammable acc. to DIN 4102 B1**



Technical Drawing



Connections



Construction



### Material

- spiral: spring steel wire
- wall: pure polyester polyurethane (acc. to DIN ISO 4649 more abrasion-resistant in comparison to polyether polyurethane)
- wall thickness between spirals approx. 1.7 - 2.1 mm, depending on DN

### Applications

- for increased requirements of abrasion resistance and durability
- Transport hose for problematic media, e.g. sand, gravel, grain, granules
- Suction & transport hose for extremely abrasive media
- Flat-roof gravelling
- Working hose for silo vehicles and cargo depots

### Properties

- acc. to DIN 26057
-

- hardly inflammable acc. to DIN 4102 B1
- extremely abrasion resistant via specific reinforcements underneath the spiral
- microbe-resistant
- permanently antistatic, surface resistance < 10<sup>9</sup> Ohm
- heavy
- flexible
- smooth inner lining, optimum flow characteristics
- high vacuum and apex pressure resistance
- highly durable, long service lives
- halogen free
- generally good UV and ozone resistance
- good resistance to chemicals, oil and fuel

### Temperature Range

- -40°C to +90°C
- peaks to +125°C

### Product Variations (\*\*Please replace “x” with your desired hose length.)

DN	op. pressure	vacuum	bend radius	outer Ø	weight/m	old article no.	**new article no.	stock length	max. production length
	bar	bar	mm	mm	kg			m	m
32	4,85	0,94	80	42	0,66	114-032-101	000158:32:x	5/7,5/10	20
38	4,39	0,94	95	48	0,78	114-038-101	000158:38:x	5/7,5/10/15	20
40	4,27	0,94	100	50	0,83	114-040-101	000158:40:x	5/7,5/10/15/20	20
45	4,1	0,94	115	55	0,92	114-045-101	000158:45:x	5/7,5/10/15	20
50	4,02	0,94	124	60	1,02	114-050-101	000158:50:x	/	20
51	4	0,94	125	61	1,04	114-051-101	000158:51:x	2,5/5/7,5/10/15/20	20
55	3,75	0,89	140	65	1,1	114-055-101	000158:55:x	2,5/5/7,5/10/15	20
60	3,6	0,89	150	70	1,2	114-060-101	000158:60:x	2,5/5/7,5/10/15/20	20
65	3,3	0,89	165	75	1,29	114-065-101	000158:65:x	2,5/5/7,5/10/15	20
70	3,15	0,89	175	80	1,38	114-070-101	000158:70:x	2,5/5/7,5/10/15	20
75	2,95	0,89	188	85	1,48	114-075-101	000158:75:x	/	20
76	2,92	0,89	190	87	1,5	114-076-101	000158:76:x	2,5/5/7,5/10/15	20
80	2,77	0,89	200	93	1,93	114-080-101	000158:80:x	2,5/5/7,5/10/15	20
90	2,4	0,89	225	103	2,16	114-090-101	000158:90:x	2,5/5/7,5/10/15	20
100	2,15	0,88	238	113	2,53	114-100-101	000158:100:x	/	20
102	2,1	0,87	250	115	2,6	114-102-101	000158:102:x	2,5/5/7,5/10/15/20	20
110	1,95	0,87	275	124	2,82	114-110-101	000158:110:x	2,5/5/7,5/10	20
115	1,8	0,87	290	129	2,94	114-115-101	000158:115:x	2,5/5/7,5/10	20
120	1,65	0,87	300	134	3,07	114-120-101	000158:120:x	2,5/5/7,5/10	20
125	1,65	0,87	311	138	3,34	114-125-101	000158:125:x	/	20
127	1,65	0,87	315	140	3,44	114-127-101	000158:127:x	2,5/5/7,5/10/15/20	20
130	1,65	0,84	325	143	3,54	114-130-101	000158:130:x	/	20
140	1,5	0,83	350	153	3,81	114-140-101	000158:140:x	2,5/5/7,5/10	20
150	1,5	0,82	434	165	4,08	114-150-101	000158:150:x	/	20
152	1,5	0,82	450	167	4,13	114-152-101	000158:152:x	2,5/5/7,5/10/15/20	20
160	1,35	0,81	500	175	4,81	114-160-101	000158:160:x	2,5/5/7,5/10	20
170	1,2	0,8	600	185	5,1	114-170-101	000158:170:x	/	20
175	1,2	0,79	650	190	5,25	114-175-101	000158:175:x	/	20
180	1,2	0,77	700	195	5,4	114-180-101	000158:180:x	2,5/5/7,5/10	20
200	1,07	0,68	918	217	6,3	114-200-101	000158:200:x	/	15

203	1,05	0,66	950	220	6,43	114-203-101	000158:203:x	2,5/5/7,5/10/15	15
225	0,9	0,58	1150	241	7,11	114-225-101	000158:225:x	2,5/5/7,5/10	10
250	0,9	0,51	1300	267	7,91	114-250-101	000158:250:x	2,5/5/7,5/10	10
254	0,88	0,5	1325	271	8,04	114-254-101	000158:254:x	/	10
275	0,75	0,47	1450	292	8,68	114-275-101	000158:275:x	/	10
300	0,6	0,42	1600	317	9,45	114-300-101	000158:300:x	2,5/5/7,5/10	10

All data refers to a medium and ambient temperature of +20 °C.

\* Refers to the inner hose lining

Subject to technical changes and colour deviations.

#### Available on request

- Available on request in other lengths, sizes.