

Flamex B-F se


PU Film Hose, PU Foil Hose, light duty, highly flexible and compressible, hardly inflammable acc. to DIN 4102 B1



Technical Drawing



Connections



Construction



Material

- spiral: spring steel wire
- wall: pure polyester polyurethane (acc. to DIN ISO 4649 more abrasion-resistant in comparison to polyether polyurethane)
- wall thickness between spirals approx. 0.5 mm

Applications

- Hardly inflammable transport hose for abrasive solids
- Wood processing machines
- Shavings extractions in wood processing
- Protective hose against mechanical wear

Properties

- acc. to DIN 26057
- smallest bending radii
- hardly inflammable acc. to DIN 4102 B1
-

- acc. to requirements of the Holz-BG standard, BGI 739-2
- symmetrical fold behaviour
- highly flexible
- halogen free
- optimum flow characteristics
- extremely compressable to approx. 1:4
- very light
- permanently kink resistant
- generally good UV and ozone resistance
- high tensile strength
- highly abrasion-resistant
- good resistance to chemicals, oil and fuel

Temperature Range

- -40°C to +90°C
- peaks to +125°C

Product Variations (**Please replace “x” with your desired hose length.)

DN	op. pressure	vacuum	bend radius	outer Ø	weight/m	old article no.	**new article no.	stock length	max. production length
	bar	bar	mm	mm	kg			m	m
40	0,82	0,24	20	46	0,26	310-040-601	000382:40:x	5/10/15	25
45	0,8	0,22	22	51	0,28	310-045-601	000382:45:x	/	25
50	0,79	0,21	24	56	0,31	310-050-601	000382:50:x	/	25
51	0,78	0,2	25	57	0,32	310-051-601	000382:51:x	5/10/15	25
60	0,76	0,19	35	68	0,37	310-060-601	000382:60:x	5/10/15	25
63	0,72	0,17	37	71	0,39	310-063-601	000382:63:x	/	25
65	0,68	0,16	38	73	0,4	310-065-601	000382:65:x	5/10	25
70	0,61	0,16	40	78	0,43	310-070-601	000382:70:x	5/10/15	25
75	0,61	0,15	42	82	0,5	310-075-601	000382:75:x	/	25
76	0,61	0,13	43	83	0,52	310-076-601	000382:76:x	5/10	25
80	0,53	0,13	45	88	0,55	310-080-601	000382:80:x	5/10/15/20	25
90	0,46	0,09	50	99	0,61	310-090-601	000382:90:x	5/10	25
100	0,46	0,09	53	106	0,67	310-100-601	000382:100:x	/	25
102	0,46	0,09	55	108	0,69	310-102-601	000382:102:x	5/10/15/20	25
110	0,38	0,09	60	119	0,75	310-110-601	000382:110:x	5/10/15	25
115	0,38	0,09	63	124	0,78	310-115-601	000382:115:x	5/10	25
120	0,38	0,09	65	129	0,81	310-120-601	000382:120:x	5/10/15/20	25
125	0,38	0,09	67	135	0,83	310-125-601	000382:125:x	/	25
127	0,38	0,09	68	136	0,85	310-127-601	000382:127:x	5/10/15	25
130	0,3	0,09	70	139	0,88	310-130-601	000382:130:x	5/10	25
140	0,3	0,06	75	149	0,95	310-140-601	000382:140:x	5/10/15	25
150	0,3	0,06	78	157	1,01	310-150-601	000382:150:x	/	25
152	0,3	0,06	80	159	1,02	310-152-601	000382:152:x	5/10/15	25
160	0,3	0,06	85	169	1,08	310-160-601	000382:160:x	5/10/15	25
170	0,23	0,06	90	179	1,07	310-170-601	000382:170:x	5/10	25
175	0,23	0,06	93	184	1,1	310-175-601	000382:175:x	/	25
180	0,23	0,06	95	189	1,13	310-180-601	000382:180:x	5/10/15	25
200	0,23	0,06	103	208	1,24	310-200-601	000382:200:x	/	25
203	0,23	0,06	105	210	1,26	310-203-601	000382:203:x	5/10/15	25
225	0,15	0,03	118	235	1,41	310-225-601	000382:225:x	5/10	25

250	0,15	0,03	128	257	1,56	310-250-601	000382:250:x	/	25
254	0,15	0,03	130	260	1,58	310-254-601	000382:254:x	5/10/15	25
280	0,15	0,03	145	290	1,92	310-280-601	000382:280:x	5/10	25
300	0,14	0,03	155	310	2,07	310-300-601	000382:300:x	5/10	25
350	0,12	0,02	180	360	2,4	310-350-601	000382:350:x	5/10	25
400	0,12	0,02	210	410	2,74	310-400-601	000382:400:x	5/10	25

All data refers to a medium and ambient temperature of +20 °C.
* Refers to the inner hose lining
Subject to technical changes and colour deviations.

Available from stock

- from DN 90 compressed and net-packed

Available on request

- Available on request in other lengths, sizes.