



Combiflex Clamp Connection Hinged Clamp

for clamp connections according to DIN 32676 series A

Product Details

Construction / Material

- Specification of the connection solution: Liquid-tight connection
- Clamp Design: Clamp with hinge, Clamp with screw lock, Clamping screw in sizes M5-M10 designed as slotted hexagon screw
- Material of the clamp: Material complies with the food regulations of DIN 32676 Series A, Stainless steel
 1.4301

Properties

- · Chemical Properties: odourless and tasteless, good resistance to chemicals
- Other: can be sterilised with superheated steam

Operating Temperature

Delivery Information

Application Areas

Customizing Options

Article Variants

Article number	DN of the hose mm	Piece weight kg	Connection mm mm
002463	40	0.23	40
002466	50	0.31	50
002470	65	0.31	65

Article numl	ber DN of the		ht Connection mm mm	
002474	80	0.41	80	
002478	100	0.41	100	
002481	125	1.17	125	
005987	150	1.34	150	

Subject to technical changes and colour deviations

Delivery Variants

Available in other lengths, other nominal diameters, with customer-specific customer-specific imprint.

Individual consultation

We offer consultation by phone:

+49 209 97077-112

Address Headquarters

Masterflex SE Willy-Brandt-Allee 300 45981 Gelsenkirchen



Product requests via masterflex.de/en