



## Master-Grip Hose Clamp, screwable

Special clamp for fastening light and medium-weight, right-handed spiral hoses such as Flamex B-se, Flamex B-F se, Master-PUR Trivolution, Master-PVC and Master-SANTO

### Product Details

#### Construction / Material

- Specification of the connection solution: largely tension-resistant and largely leak-proof connection due to bridge profiles
- Clamp Design: Clamp with housing, worm thread and clamping screw, Clamping screw in sizes M5-M10 designed as slotted hexagon screw, Clamp band with single or multiple bridges, spot welded bridge
- Material of the clamp: Steel

#### Properties

- Chemical Properties: rust-protected
- Other: easy to assemble

#### Operating Temperature

#### Delivery Information

#### Application Areas

#### Customizing Options

### Article Variants

Article number	DN of the hose mm	Type	Clamping range mm
001626	35/40	for right-handed hoses in DN 35/40	35 - 55

Article number	DN of the hose mm	Type	Clamping range mm
001629	45/50	for right-handed hoses in DN 45/50	45 - 65
001633	55/60	for right-handed hoses in DN 55/60	55 - 75
001636	65/70	for right-handed hoses in DN 65/70	65 - 85
001639	75/80	for right-handed hoses in DN 75/80	75 - 95
001642	90	for right-handed hoses in DN 90	85 - 105
001646	100	for right-handed hoses in DN 100	95 - 115
001649	110/115	for right-handed hoses in DN 110/115	105 - 125
001651	120/125	for right-handed hoses in DN 120/125	115 - 135
001653	130	for right-handed hoses in DN 130	125 - 145
001655	140	for right-handed hoses in DN 140	135 - 155
001657	150	for right-handed hoses in DN 150	145 - 165
001659	160	for right-handed hoses in DN 160	155 - 175
001661	170/175	for right-handed hoses in DN 170/175	165 - 185
001663	180	for right-handed hoses in DN 180	175 - 195
001667	200	for right-handed hoses in DN 200	195 - 215
001670	215	for right-handed hoses in DN 215	205 - 225
001672	220/225	for right-handed hoses in DN 220/225	215 - 235
001674	250	for right-handed hoses in DN 250	245 - 265
001676	275	for right-handed hoses in DN 275	265 - 285
001679	300	for right-handed hoses in DN 300	295 - 315
001682	310/315	for right-handed hoses in DN 310/315	305 - 325
001684	325	for right-handed hoses in DN 325	315 - 335
001685	350	for right-handed hoses in DN 350	345 - 365
001687	375	for right-handed hoses in DN 375	365 - 385
001688	400	for right-handed hoses in DN 400	395 - 415
001691	450	for right-handed hoses in DN 450	445 - 465
001692	500	for right-handed hoses in DN 500	495 - 515
001677	280	/	275 - 280

Subject to technical changes and colour deviations

## Delivery Variants

Available in other lengths, other nominal diameters, with customer-specific customer-specific imprint.

### Individual consultation

We offer consultation by  
phone:  
**+49 209 97077-112**

Product requests via  
[masterflex.de/en](https://www.masterflex.de/en)

### Address Headquarters

Masterflex SE  
Willy-Brandt-Allee 300  
45981 Gelsenkirchen

