



Carflex 200

Article Master No.: 000334

Exhaust gas hose for exhaust fumes/gases up to 200 °C



hydrolysis resistant



microbe resistant



compressible



very flexible



light



moderately pressure resistant

Product Details

Construction / Material

- Type of construction: Spiral hose with clamping profile
- Design of the helix: metal band, formed as a clamping profile
- Material of the helix: Steel strip, hot-dip galvanised
- Design of the external spiral: covered with a plastic profile to protect against scratches
- Execution of the wall: coated, Coating of neoprene
- Material of the wall: Polyester fabric

Properties

- Chemical Properties: very good resistance to chemicals
- Mechanical Properties: compressible approx. 1:5, Resistance to vibrations and mechanical-dynamic load (cycle operation)
- Flexibility: very flexible
- Weight: light
- Pressure Resistance: moderately pressure resistant
- Colour: Black hose wall, blue scuff protection profile

Operating Temperature

- Temperature Range: 0 - 200

- short-term maximum temperature: peaks to 200 °C flue gas temperature, for proper use flue gas funnels are required and a sufficient supply of fresh air (approx. 50% related to the maximum specified temperature)

Delivery Information

- Delivery, type of production: Order-related production

Application Areas

- Areas of application: Automotive, Ventilation & air-conditioning

Customizing Options

- optional item modification (on request): other lengths, other nominal widths, other colours, other spiral distance, with stainless steel spiral

Article Variants

Extended Article Number	Article number	Nominal Size (DN) mm	Bending radius* mm	Weight kg/m	Negative pressure bar	Max. Production length m	Stock Lengths m
000334:63:x	000334	63	38	0.55	0.23	25.00	2.50, 5.00, 7.50, 10, 12, 15
000334:75:x	000334	75	46	0.60	0.18	25.00	2.50, 5.00, 7.50, 10, 12, 15
000334:80:x	000334	80	48	0.63	0.15	25.00	2.50, 5.00, 7.50, 10, 12, 15
000334:100:x	000334	100	60	0.79	0.10	25.00	2.50, 5.00, 7.50, 10, 12, 15
000334:125:x	000334	125	75	0.95	0.06	25.00	2.50, 5.00, 7.50, 10, 12, 15
000334:150:x	000334	150	90	1.47	0.04	25.00	2.50, 5.00, 7.50, 10, 12, 15
000334:200:x	000334	200	120	1.76	0.03	25.00	2.50, 5.00, 7.50, 10, 12, 15

All data refer to a medium and ambient temperature of +20°C.
Specification of the bending radius related to the inside of the hose bend
Subject to technical changes and colour deviations

Delivery Variants

Available in other lengths, other nominal diameters, with customer-specific customer-specific imprint.

Possible Connection Elements



Hose connector
Sheet steel connector for extending, connecting and joining light to medium-weight hoses



Hose Reducer, symmetrical
Hose reducer for extending, connecting and joining light to medium weight hoses



Clip-Grip Hose Clamp, screwable
Screwable clamp for attaching all hose types from the Master-Clip series to mobile and stationary systems



Clip-Grip Hose Clamp, screwable, Steel quality W4, stainless steel 1.4301
screwable clamp for attaching all hose types from the Master-Clip series to mobile and stationary systems



Clip-Grip Quick-Fix Clamp
Special clamp for attaching all hose types from the Master-Clip series to mobile and stationary units.

Individual consultation

We offer consultation by
phone:
+49 209 97077-112

Product requests via
[masterflex.de/en](https://www.masterflex.de/en)

Address Headquarters

Masterflex SE
Willy-Brandt-Allee 300
45981 Gelsenkirchen

