



## Combiflex Cast-on PU Fixed Flange Food

fixed flange for all Master-PUR Food hose types, approved for direct food contact EU 10/2011, for counterflanges acc. to DIN 2632 / DIN 2633 / DIN 2673

### Product Details

#### Construction / Material

- Specification of the connection solution: Flange suitable for counter flange according to DIN 2632/2633, Hole pattern according to DIN 2501, Welding neck according to DIN 2673, Smooth transition between hose and flange, Connection option without cross-section narrowing, Pressure stage PN 10/16
- Execution of the sprue / collar: made of specified material
- Material of the sprue / collar: Polyurethane
- Specification of the sprue / collar: approved for direct food contact according to EU Directive 1935/2004, 10/2011 and its latest amending Directives, Material complies with the food regulations of BfR XXXIX

#### Properties

- Chemical Properties: microbe-resistant, hydrolysis resistant
- Colour: white
- Other: easy to assemble, Dissipation of electrostatic charge due to integrated earthing plate

#### Operating Temperature

- Temperature Range: -40 - 90
- short-term maximum temperature: peaks to 125 °C

#### Delivery Information

- Delivery, type of production: Various nominal widths are available ex production, individual nominal widths also ex stock

#### Application Areas

## Customizing Options

### Article Variants

Article number	DN of the flange mm	DN of the hose mm	Outer diameter of the pipe (AD) mm	Outer diameter of the sprue on the hose side (AD) mm	Piece weight kg	Bolt circle	Length mm
005502	50	50	57.00	75	0.55	125	66
001903	50	50	60.30	75	0.55	125	66
005515	65	65	76.10	90	0.69	145	76
/	65	65	76.10	105	not specified	145	76
/	80	80	88.90	105	not specified	160	76
005433	80	80	88.90	105	0.85	160	76
005617	100	100	108.00	131	1.13	180	86
005591	100	100	114.30	131	1.13	180	86
/	120	120	no data	/	not specified	/	no data
/	120	120	no data	/	not specified	/	no data
005456	125	127	133.00	156	1.00	210	92
008219	125	127	139.70	156	1.00	210	92
/	140	140	no data	/	not specified	/	no data
005548	150	150	no data	/	not specified	/	no data
/	150	150	no data	/	not specified	/	no data
/	160	160	no data	/	not specified	/	no data

Subject to technical changes and colour deviations

### Delivery Variants

Available in other lengths, other nominal diameters, with customer-specific customer-specific imprint.

#### Individual consultation

We offer consultation by phone:  
+49 209 97077-112

Product requests via [masterflex.de/en](https://www.masterflex.de/en)

#### Address Headquarters

Masterflex SE  
Willy-Brandt-Allee 300  
45981 Gelsenkirchen

