



## Combiflex PU Threaded Sockets

PU threaded connector for all Master-PUR L, Master-PUR H and Master-PUR HX hose types, based on DIN ISO 228

### Product Details

#### Construction / Material

- Specification of the connection solution: Connection thread is designed according to DIN ISO 228, Tension-resistant and largely leak-proof connection
- Execution of the sprue / collar: made of a material with high impact strength, made of abrasion resistant material
- Material of the sprue / collar: Polyurethane

#### Properties

- Chemical Properties: hydrolysis resistant, microbe-resistant
- Colour: black
- Other: reusable and replaceable, easy to assemble, Fixed version equipped with digital interface as standard. Compatible with the AMPIUS® app

#### Operating Temperature

- Temperature Range: -40 - 90
- short-term maximum temperature: peaks to 125 °C

#### Delivery Information

- Delivery, type of production: Various nominal widths are available ex production, individual nominal widths also ex stock, individual nominal widths also ex stock

#### Application Areas

#### Customizing Options

- optional item modification (on request): in permanently mounted design for liquid-tight, tension-resistant connections, other nominal widths, other colours

### Article Variants

Article number	DN of the hose mm	Connection thread (G) Zoll	Type	Piece weight kg	Length mm
001457	50	2	Hoses in version L	0.16	83
001458	65	2.5	Hoses in version L	0.23	94
001459	75	3	Hoses in version L	0.26	102
001460	100	4	Hoses in version L	0.53	124
001461	150	6	Hoses in version L	0.95	109
001462	50	2	Hoses in version H	0.16	83
001463	65	2.5	Hoses in version H	0.23	94
001464	75	3	Hoses in version H	0.26	102
001465	100	4	Hoses in version H	0.53	124
001466	125	5	Hoses in version H	0.65	100
001467	150	6	Hoses in version H	0.95	109
001468	50	2	Hoses in version HX	0.16	83
001470	65	2	Hoses in version HX	0.23	94
001471	75	2.5	Hoses in version HX	0.26	102
001472	100	2.5	Hoses in version HX	0.53	124
001474	125	3	Hoses in version HX	0.65	100
001475	150	3	Hoses in version HX	0.95	109
006943	50	4	Hoses in version Performance	0.16	83
001473	100	5	Hoses in version Performance	0.53	124

Subject to technical changes and colour deviations

### Delivery Variants

Available in other lengths, other nominal diameters, with customer-specific customer-specific imprint.

<p><b>Individual consultation</b></p> <p>We offer consultation by phone: <b>+49 209 97077-112</b></p> <p>Product requests via <a href="https://www.masterflex.de/en" style="color: white;">masterflex.de/en</a></p>	<p><b>Address Headquarters</b></p> <p>Masterflex SE Willy-Brandt-Allee 300 45981 Gelsenkirchen</p>	
---	--	---